



2115TiMAX 3/8"
AIR IMPACT WRENCH

MAXIMUM IMPACT

The new 2115TiMAX delivers best in class performance for a tool less than six inches long and weighing less than two and a half pounds. The minimal size of this tool will allow greater access to tight spaces, while the minimal weight will reduce operator fatigue...all while still delivering MAX performance.

MAX POWER

300 ft-lbs max power in reverse – that's best in class power performance

MAX CONTROL

Enhanced power settings, a feather touch trigger and patented push button forward/reverse provide maximum control

MAX RELIABILITY

FREE two-year limited warranty with tool registration

TOOL FEATURES



SPECIFICATIONS	
Max Torque (Reverse)	300 ft-lb (407 Nm) 3/8" Drive Models
	332 ft-lb (450 Nm) 1/2" Drive Models
Forward Torque Range	25 – 230 ft-lb (34 – 312 Nm) 3/8" Drive Models
	25 – 251 ft-lb (34 – 340 Nm) 1/2" Drive Models
Blows Per Minute	1,500
Maximum Free Speed	15,000 rpm
Sound Pressure (Free Speed)	89.7 dBA**
Net Weight (2115TiMAX)	2.48 lb (1.12 kg)
Overall Length	5.95" (151 mm)

AIR REQUIREMENTS	
Air Consumption, Avg.	4 cfm (113 l/min)
@ load	17 cfm (481 l/min)
Air Inlet	1/4" NPTF
Minimum Hose Size	3/8" (10 mm)



