

Ultra Power - Ultra Compact - Ultra Reliable

Ingersoll Rand® 36QMAX 1/2" & 15QMAX 3/8" Ultra-Compact Impact Wrenches

Introducing the Ingersoll Rand® 36QMAX Quiet Ultra-Compact Impact Wrench. Built on Ingersoll Rand's 100-year legacy developing industry leading tools, you can always rely on the 36QMAX. This tool has been rigorously tested, beaten up, dropped and pushed to the limits to make sure it lasts **twice as long as the competition**. With their twin hammer design, unmatched durability, superior accessibility and up to 640 ft-lbs* of nut busting torque at just 2.4 lbs, the 36QMAX and 15QMAX are not just tools you want, they are tools you need to get REAL WORK done time and time again.









Suspension

Engine Bay

Wheel Lug

Subframe bolts

Tool Features

ACCESS

There is no place for work to hide; as this compact design gives the user the access and power they need, even if the task is up, under, over, or around any awaiting obstruction.



RELIABILITY

Built on the IR Impact Wrench legacy, this tool is testing at 2X the life of competitive products available today. Backed by a 2-year warranty to prove it.

POWER-TO-WEIGHT

At 2.4 pounds this tool still manages to produce 640 ft-lbs of nut busting torque making it a power-to-weight leader in its class.

CONTROL

The one-handed forward/reverse push button and 3-mode power regulator give you max control and max performance.

Specs

Model	Drive Size, Type	Max Torque ftlb. (Nm)	Nut-Busting Torque ftlb. (Nm)	ВРМ	Free Speed (rpm)	Weight lb (kg)	Length in. (mm)	Sound Level dB(A)
36QMAX	1/2"	470 (640)	640 (870)	1300	8000	2.4 (1.1)	4.6 (117)	91.3
15QMAX*	3/8"	380 (520)	475 (650)	1350	6000	2.4 (1.1)	4.6 (117)	89.7

^{* 36}QMAX boasts 640 ft-lbs nut busting torque. 15QMAX sports 475 ft-lbs nut busting torque.

Performance at 6,2 bar (90 PSI) – Air inlet NPTF 1/4" (6 mm). Min hose size 3/8" (10 mm) Min hose size 3/8" (10 mm).





www.ingersollrand.com