



1" D-Handle Impact Wrench  
2850MAX & 2850MAX-6



**REAL TOOLS FOR REAL WORK.™**

# Powered Up, Not Weighed Down

## Ingersoll Rand 2850MAX 1" D-handle Impact Wrench

With 2,100 ft lbs of torque, the new Ingersoll Rand 2850MAX 1" D-handle Impact Wrench is our fiercest 1" wrench yet, loaded with extreme power that lasts as long as you need and continuously delivers over time. This sturdy yet lightweight impact wrench powers through bolts other tools can't. With a steel core, precision machined impact mechanism and powerful motor, the 2850MAX is solid enough to handle REAL WORK day in and day out without sacrificing power over time. But even with all that high-performance steel, the 2850MAX is still 25% lighter than the industry's leading 1" wrench, so it's easy to maneuver and causes less fatigue. No matter how tough the job, you can power through with the 2850MAX.



Heavy Truck & Tire Changing



Industrial Maintenance



Heavy Equipment



Vehicle Repair

### Tool Features

- DURABILITY**  
Chemical resistant housing & steel core design stand up to drops and harsh work environments
- RELIABILITY**  
Highly engineered design delivers the power you need over the life of the tool
- POWER**  
Solid steel impact mechanism delivers 2,100 ft lbs of torque
- ERGONOMICS**  
At 21.58 lbs, 25% lighter than the industry's leading 1" wrench
- REACH**  
6" extended anvil increases accessibility in hard to reach places (**2850MAX-6**)  
Standard anvil option available, (**2850MAX**)
- CONTROL**  
360° adjustable side handle rotates fully around the tool as the job demands
- ACCESSIBILITY**  
Swivel hose connection keeps cords from getting tangled so you can move freely around the work

### Specs

| 2850MAX & 2850MAX-6 1" Impactool™ |                  |                                    |                                    |     |                     |                   |                    |                      |
|-----------------------------------|------------------|------------------------------------|------------------------------------|-----|---------------------|-------------------|--------------------|----------------------|
| Model                             | Drive Size, Type | Max Forward Torque<br>ft.-lb. (Nm) | Max Reverse Torque<br>ft.-lb. (Nm) | BPM | Free Speed<br>(rpm) | Weight lb<br>(kg) | Length in.<br>(mm) | Sound Level<br>dB(A) |
| <b>2850MAX</b>                    | 1"               | 2000 (2715)                        | 2100 (2850)                        | 770 | 5500                | 19.41 (8.8)       | 13.1 (334)         | 96.7                 |
| <b>2850MAX-6</b>                  | 1" - 6 inch      | 2000 (2715)                        | 2100 (2850)                        | 770 | 5500                | 21.58 (9.8)       | 19.1 (486)         | 96.7                 |



irtools.com/2850MAX  
**REAL TOOLS FOR REAL WORK.**

Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results.