

New



The Ingersoll Rand Revolution Series die grinders offer an outstanding combination of value and performance, delivering impressive comfort and durability with the power required for a wide range of service, maintenance and light production applications.

- Powerful motor delivers 0.30 kW (0.40 HP).
- 25 000 rpm free speed.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- The low weight of this tool will reduce operator fatigue.
- Integral trigger safety lock prevents accidental tool start.
- Rear exhaust directs air away from the operator.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	325XC4A
Ordering number	45763521
Collet capacity	1/4 in / 6 mm
Other available versions:	330XC4A
- 30 000 rpm	

PERFORMANCE

Rated power	0.40 HP / 0.30 kW
Free speed	25 000 rpm

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	8.0 CFM / 3.8 L/s
Air consumption at load	33.0 CFM / 15.6 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744)	78.6 / 89.6 dB(A)
Vibration level / measurement uncertainty (ISO28927)	< 2.5 m/s ²

WEIGHT & DIMENSIONS

Tool weight	1.36 lb / 0.62 kg
Tool length	9.60 in / 244 mm
Shipping weight	2.18 lb / 0.99 kg
Shipping dimensions (L x W x H)	261 x 76 x 58 mm
UPC / EAN code	6 63023 08237 0
Origin	Made in China



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS_325XC4A_EN_18/05/2011




DG110-700-G2
03641743
Erickson collet, 1/8" (3,2 mm)




DG110-700-6MM
04261053
Erickson collet, 6 mm



DG110-700-G4
03641602
Erickson collet, 1/4" (6.35 mm)



RG1-26
80227200
Collet body wrench



301-69
04552683
Collet nut wrench



LG1-K284
80152119
Piped-away exhaust kit



33104-45
92938760
Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1.5 ft)



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



67-LBK1
04637344
Lubricant kit for angle head tools



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



67-4T
04637336
Grease for high-speed angle heads