



INSIGHTqcTM CONTROLLER

Simple, Flexible and Capable Solutions

SIMPLY INSIGHTFUL

When trying to achieve simple manufacturing goals in a complex manufacturing world, taking control of and understanding the fastening process doesn't have to be complicated. The new Ingersoll Rand® INSIGHTqc™ is different, by design. The INSIGHTqc[™] controller is designed to be easy to use, easy to integrate, and provide a common platform to meet the global assembly needs of our customers. This controller offers advanced tightening control and a simple user experience to improve efficiency on production lines, and get the job done right, every time.



SIMPLE

EXPERTS NOT REQUIRED

EASILY IMPLEMENT CHANGE

Easy line integration

FLEXIBLE

Reduce line rebalancing costs

Remove device dependency

Enhanced to Svnc several tools to 1 independent controller

REQUIREMENTS

WHAT DOES THIS MEAN TO ME?

WHY DO I

CARE?

- **HOW DOES INGERSOLL** RAND OFFER THIS?
- Reduce errors and downtime

and installation costs

- Remove user dependencies
- Intuitive, Visual Programming Interface
- Plug and Play Accessories and Protocols
- Backwards Capability
- Integrated Backup and Recovery
- Bundled Controller Options
- Context Specific Integrated HELP

Save on selection, training

- Web Based programming use any operating system via any browser
- Meets current industry communication needs
- Adjustable to meet any tightening control requirements
- Integrated logic controls
- Easy hardware and software upgrades

MEET YOUR

Get the job right, every time

CAPABLE

- Assurance via traceability
- Optimize your productivity
- Seamlessly control the Multi Spindle Fastening Solutions
- Touch Screen Interface
- Industry leading cycle data storage
- Robust audit and system logs
- Advanced tightening strategies and features
- Onboard diagnostics
- Integrated statistical process controls
- Preventative maintenance alarms
- Configurable email alerts

The web-based software eliminates device dependencies and enables full programming capability with any device that can run an Internet browser, including smart phones, tablets or computers. The INSIGHTqc™ controller is easy to integrate with the manufacturing line, provides flexible logic controls for job sequencing, and helps reduce line rebalancing costs through a simple and intuitive user interface. The INSIGHTqc™ Controller Platform has been enhanced to support both single & multi-spindle fastening applications, syncing multiple uses and applications to one controller platform.

Bottom line, the INSIGHTqc™ controller is a Simply Insightful solution.

CAPABILITIES


	Standard	F	M	FM		Standard	F	M	FM
Software Feature	•	•	•	•	License Update	•	•	•	•
Home Screen	•	•	•	 License Activate 		•	•	•	•
JOB Setup	•	•	•	•	Date & Time Settings	•	•	•	•
PSET Setup	•	•	•	•	System Initialization	•	•	•	•
ALL Tighteing Strategies	•	•	•	•	Spindle Management	•	•	•	•
Quick Programming	•	•	•	•	IP Address Settings	•	•	•	•
Advanced Programming	•	•	•	•	Email Alerts	•	•	•	•
Cycle Results	•	•	•	•	Digital IO Settings	•	•	•	•
JOB Results	•	•	•	•	EOR Data Out	•	•	•	•
Audit Log	•	•	•	•	Barcode	•	•	•	•
Event Log	•	•	•	•	User Managmeent	•	•	•	•
System Diagnostics	•	•	•	•	System Logs		•		•
Tool Diagnostics	•	•	•	•	Fieldbus Diagnostics		•		•
Digital IO Diagnostics	•	•	•	•	Fieldbus Settings		•		•
Statistics Settings	•	•	•	•	Ethernet IP		•		•
Statistics Summary	•	•	•	•					
Statistics Alarm Settings	•	•	•	•	ProfiBus		•		•
Statistics Alarm Summary	•	•	•	•					
Backup and Restore	•	•	•	•	MES Protocols Settings			•	•
Firmware Update	•	•	•	•	Atlas Copco Open Protocol			•	•
Preventative Maintenance Alarms	•	•	•	•	Atlas Copco ToolsNet			•	•
Tool Calibration	•	•	•	•	VW XML 2.1			•	•
Factory Reset	•	•	•	•	Nissan Serial EOR			•	•
Network System Discovery	•	•	•	•					

STATISTICAL PROCESS CONTROLS Statistic Description Status Statistical average - used to derive the central tendency of the tightening data of a Mean Calculated as (6* sigma / Mean) * 100 on a particular PSET Capability Indicates the % of the cycles that have a cycle result of PASS from the sample Pass % population of a particular PSET Indicates the % of the cycles that have a cycle result of FAIL from the sample Fail % population of a particular PSET Calculated as: MEAN Result Value - TARGET Result Value for a particular PSET Mean Shift Range Calculated as: MAX Result Value - MIN Result Value of a particular PSET. Standard The calculated standard deviation (σ) of the Result Value of a particular PSET. Deviation (σ) PP Process Performance, calculated as: (USL - LSL) / (6 * σ) CAM Calculated as: (USL - USL) / (6* (W / d * S)) Process Performance Index, Calculated as: MIN ((MEAN - LSL) / (3 * σ) OR (USL PPK - MEAN) / (3 * σ)


TORQUE/ANGLE CONTROL




PREVAILING TORQUE



STICK SLIP DETECTION



GRADIENT/ SLOPE ANALYSIS





SPECIFICATIONS





INSIGHTqc™ CONTROLLER

BY THE NUMBERS

Software







Steps per **PSET**







(IR)



• PC License

User Logins

- Barcode function: USB, Serial, Ethernet
- Manual barcode entry optio

Logic rules for JOB sequencing

- ▼ Tubenut controls (configurable modes) ✓ Multi-language support
- Quick programming mode
- Advanced programming mode

- Unrestricted programming from controller or remot
- Embedded, context-specific hpl
- Same hardware for single or multi spindle options
- Onboard tool diagnostic
- Trade transfer over open protocol

ONBOARD DATA STORAGE

- Removable SSD Card that stores ALL settings and dat
- Complete controller settings and data recovery through SSD swap
- Tightening curve displayed on Home screen of controlle
- ✓ Full USB Backup and Restore Function

- 500k
- Audit Logs Tightening Results
- Event Logs Tightening Curves
- System Logs

Connectivity

Fieldbus



Ethernet IP, ProfiNet,

MES Protocol Options

Open Protocol, Ford Open Protocol, ToolsNet, Toyota PokeYoke, VW XML, IR Ethernet EOR, & Nissan Serial EOR

Hardware











Tool Families



10.9 Volume 10.9 dm²



4 USB 2.0 Ports



Touch Screen 7 Inch Color



Et hernet Ports 10/100, 10/100/1K



ONE CONTROLLER

COUNTLESS CAPABILITIES

Ingersoll Rand's INSIGHTqc™ Controller Platform has been enhanced to support both Single-Spindle and Multi-Spindle fastening applications, syncing multiple uses and applications to one single controller platform. Starting with its simplified setup, this upgrade reduces wasted time and allows its users to quickly adapt to changing needs on the spot—all without the burden of managing multiple platforms.

- Simplicity: Now offered as a single controller platform for Multi- and Single-Spindle applications, the simplicity of the INSIGHTqc™ Controller Platform cannot be overstated. By using a single controller to navigate multiple needs and functions, this advanced system simplifies setup, streamlines operations and empowers you to complete intricate jobs accurately.
- Flexibility: Designed with the ability to quickly adapt to every changing need without the burden of managing multiple platforms, this single controller system features first-rate flexibility and decreased downtime. And, thanks to its flexibility in programming, users can customize and adjust settings based on their specific needs.
- Productivity: Backed by a unified controller platform that's easy to use and navigate, the Multi-Spindle fastening application works cohesively with the INSIGHTqc™ controller to keep your efficiency at an all-time high. Users will appreciate its ability to easily modify program parameters to switch between different profiles, making it simple to accommodate variations in fastener types, torque requirements or assembly configurations.
- Performance: As a direct result of its ability to apply torque with precision and consistency across all spindles, this newly enhanced system reduces the likelihood of product failures, loose connections or performance issues, resulting in higher product reliability and overall quality.

Our newly enhanced INSIGHTqc™ controller system works seamlessly with our Multi-Spindle Fastening Solutions to save time, effort and space—without sacrificing Ingersoll Rand's trademark toughness and reliability.









CONTROLLER MODELS

The INSIGHTqc™ Controller is 100% compatible with our QE and QM tools. With the INSIGHTqc™, these tools will have 500K tightening records and 500K tightening traces - compared to 10 to 30K in competitors' products – which will let users understand all facets of the tightening process – torque, angle, time and date.

	SYSTEM OPTIONS			FIELDBUS	OPTIONS	MES OPTIONS					
Model	Series	Display	Power	Hardware	Ethernet/P	ProfiNet	IR Ethernet EOR	Atlas Copco Open Protocol	ToolsNet	VW XML 2.1	Nissan SerialEOR
QCD11	QC	Display	120V AC	Standard			•				
QCD11-F	QC	Display	120V AC	Standard	•	•	•				
QCD11-M	QC	Display	120V AC	Standard			•	•	•	•	•
QCD11-FM	QC	Display	120V AC	Standard	•	•	•	•	•	•	•
QCD21	QC	Display	230V AC	Standard	•	•	•				
QCD21-F	QC	Display	230V AC	Standard	•	•	•				
QCD21-M	QC	Display	230V AC	Standard			•	•	•	•	•
QCD21-FM	QC	Display	230V AC	Standard	•	•	•	•	•	•	•

Multi-Spindle Software License

art Reference	Description	вом
MS-SW-OPT-1	Multi Spindle Software License, OPT – 1	Receptacle, flash drive
MS-SW-OPT-2	Multi Spindle Software License, OPT – 2	Adapter, USB to Ethernet Activation Card Information Label Label
MS-SW-OPT-3	Multi Spindle Software License, OPT – 3	1 5-900-72-72-0


If customer wants to support 10 spindles, we can cater to requirements by providing licenses in one of the below combination :

- OPT 3 X 3 + OPT 1
- OPT 2 X 5


*In this case License Option (OPT) represents number of spindle licenses

DC ELECTRIC NUTRUNNERS

QE2 Series DC electric nutrunners



OE Series DC electric nutrunners



SYSTEM ACCESSORIES

The INSIGHTqc™ Controller provides optimal flexibility for the workstation with compatibility to a variety of plug n play accessories to maximize productivity for your manufacturing line. A variety of cables and extension cables are available to customize your production setup.

Model	Description	Order Number
QC-SKTR	Socket Tray, 4 Position	47615828001
QC-ADPT-1	Serial Interface Adaptor	47601630001
QC-DIO-8CH	Digital I/O Box, 8 Channel	47617332001
QC-BC-SCAN-1	Bar Code Scanner, Cabled USB; HD	47625754001
QC-BC-SCAN-2	Bar Code Scanner, Cabled USB; LD	47625755001
QC-BC-SCAN-WL	Bar Code Scanner, HD, Wireless with USB Cradle	47625756001
QC-DIO-366-K	DIO Box Mounting Bracket Kit	47628739001





USB to Serial Adapter

Socket Tray



TOOL CABLES

	(3m)		(10m)	
DC Tool Cables				
Tool Cable (QE2)	CPS2-CORD-3M	CPS2-CORD-6M	CPS2-CORD-10M	
90 tool cable (qe2)	-	CPS2-CORD-6M-90		
Tool cable (qm, qe4/6/8)	GEA40-CORD-3M	GEA40-CORD-6M	GEA40-CORD-10M	
90 cool cable (qm,qe4/6/8)	GEA40-CORD-3M-90	GEA50-CORD-6M-90	GEA40-CORDX-10-90	
	(10m)	(20m)	(40m)	
DC Tool Extenson Cables				
Extension cable	GEA40-EXT-10M	GEA40-EXT-20M	GEA40-EXT-40M	
	(50")	936		
90 extension cable***	GEA40-INT-01			

^{*** 90} degree extension cable requires a tool cable. Other lengths available.





(IR) Ingersoll Rand。