



INSIGHTqcT[™] SERIES — Calibration Equipment

FASTENING INDUSTRY

Competition is driving product quality requirements to new levels. Meeting these demands requires keeping your processes in control and your tools working within specifications.

THE SOLUTION

INSIGHTqcT™ Series calibration equipment

Our INSIGHTqcT™ Series calibration equipment is the ideal quality control companion for assembly operations with stringent torque control standards. Choose from our offering of easy-to-use torque testers, analyzers, transducers, and joint kits to set up and calibrate your full portfolio of precision tools.

IQCTT SERIES TORQUE TESTERS

The IQCTT Series of torque testers includes four different models with integrated transducers that allow rapid and accurate torque checking of fastening tools from 0.1 to 30 Nm (1 to 265 in-lb). The IQCTT's enhanced features include track and peak modes for most hand and power tools, a pulse mode that measures and counts pulses for pulse tools, and a click mode for hand-click wrenches. Included trace and statistical functions support even the most detailed joint analysis and proper decision making.

IQCTA SERIES TORQUE ANALYZER

The IQCTA Series torque analyzer shares the same compact, sleek design and impressive feature set, but is designed for portability. It can dynamically measure and record the output of precision fastening tools on the application or the workbench in both directions when coupled with our automatically recognized Smart or







Industry Standard transducers. Joint simulators are also available to emulate different joint rates from hard to soft and can be used with both stationary and rotary transducers when working away from the application.

PORTFOLIO OVERVIEW

Ingersoll Rand® offers a full line of production fastening equipment, including pneumatic and electric screwdrivers, nutrunners, drills, riveters, pulse tools, as well as hand-held and multispindle fixtured DC nutrunners. Whether you need a solution for a single, specific application or an entire assembly line, you can trust our century of tool design experience to meet your needs.





CALIBRATION EQUIPMENT



IQCTT TESTER

- Compact bench-mount unit
- Integrated torque transducer in (4) ranges from 1 to 30 Nm
- · Large color screen
- Simple programming and navigation
- Full statistical and tightening trace analysis
- · Variable rate rundown adapter included
- Rechargeable Li-Ion battery with auto-shutdown feature
- USB port for data export

Ideal for testing and calibration of lower torque assembly tools in a tool crib, calibration lab, or workstation.



IQCTA ANALYZER

- Lightweight portable unit
- · Compatible with full range of Industry Standard (IS) and Smart external transducers
- Large color screen
- · Simple programming and navigation
- · Full statistical and tightening trace analysis
- Rechargeable Li-Ion battery with auto-shutdown feature
- USB port for data export

Ideal for use with a broad range of external transducers to test output of assembly tools on the application or wherever torque verification is reauired.



ACCESSORIES

- Rotary transducers
- Stationary transducers
- · Joint simulator kits
- Rundown adapters
- Transducer cables
- Battery charger
- Calibration service

Take advantage of our extensive line of accessories and services to optimize your assembly and quality assurance processes.

OTHER ACCESSORIES

TRANSDUCERS

Rotarv Stationary

JOINT SIMULATION KITS

Rundown Adaptor

Cable - IS transducer

Neck strap Port saver - 25 pin Power Supply

ETA2-TC ETA2-STRAP ETA2-P525 IQC-PS5







Rotary





INSIGHTqcT™ SERIES TORQUE

TESTERS AND ANALYZERS

POWER AND HAND TOOL COMPATIBILITY-

means only one system is needed to setup and calibrate all of your precision tools

FULL STATISTICAL CAPABILITIES

Include Count, Range, Mean, MIN, MAX, Standard Deviation, Cm, Cmk, Cp, Cpk

COMPACT AND LIGHTWEIGHT with

rechargeable Li-lon battery provides ease of use and portability on the assembly line and space savings on the workbench

LARGE COLOR SCREEN

shows clear, easy-to-read test results, menus, and traces


SOFT-TOUCH KEYPAD and intuitive

menus make navigation and test setup quick and simple

AUDIBLE AND VISIBLE INDICATORS

give High, Low, and Pass cycle status





- Monitors bi-directional torque, angle, time, RPM & pulse count
- Supports onboard trace analysis and data export
- Reads in peak, click, pulse, or track mode
- Stores 999 time-stamped readings
- Auto-recognition of Smart transducers
- Selectable filter frequencies
- USB data export for readings and trace data
- Configurable Auto-print function via USB
- Eleven (11) units of measure
- Adjustable power-save settings
- Multi-language support for English, French, German, Italian, and Spanish

IQCTA SERIES - INSIGHTqcT™ TORQUE ANALYZER

	Model	Compatible Transducer	Data Transfer	Auto Recognition	Screen Size (mm)
_	IQCTA	TRD TR TRDA TSD TS Industry Standard UTA	USB (csv) Printer	Yes	85x50 mm

Rotary transducers



IQCTT SERIES – INSIGHTqcT™ TORQUE TESTER

Model	in-lb Range	Nm Range	Rundown Adaptor*	Service Kit
IQCTT-1	0.88 - 8.8	0.1 - 1	ETT-RA-1	ETT-RA-1-KIT
IQCTT-4	3.50 - 35	0.4 - 4	ETT-RA-4	ETT-RA-4-KIT
IQCTT-12	10.6 - 106	1.2 - 12	ETT-RA-12	ETT-RA-12-KIT
IQCTT-30	26.5 - 265	3.0 - 30	ETT-RA-30	ETT-RA-30-KIT

^{*} IQCTT tester includes rundown adaptor, carrying case, power supply, manuals, and a certificate of calibration. IQCTA analyzer includes carrying case, power supply, manuals, and neck strap.

QUICK DOWNLOAD OF results to printer or USB for data analysis, graphing,

documentation, or calibration

Dimensions

209 x 194 x 78 mm

Weight 2.2 lb / 1.0 kg (IQCTA) 4.5 lb / 2.1 kg (IQCTT)

WSCOTTLUT B manage int B man

TRANSDUCERS

ROTARY	Industry Standard	Smart Tran Torque Only	sducers Torque and Angle	(in-lb) ft-lb	Nm	in
	TR2H4	-	-	(1.0 - 18)	0.10 - 2	1/4
	TR5H4	TRD5H4	TRDA5H4	(2.2 - 44)	0.25 - 5	1/4
	TR20H4	TRD20H4	TRDA20H4	(9.0 - 180)	1 - 20	1/4
	TR20S4	TRD20S4	TRDA20S4	(9.0 - 180)	1 - 20	1/4
	TR75S6	TRD75S6	TRDA75S6	2.8 - 55	3.8 - 75	3/8
	TR180S8	TRD180S8	TRDA180S8	6.7 - 133	9 - 180	1/2
	TR250S12	-	_	9.2 - 185	12.5 - 250	3/4
	TR500S12	TRD500S12	TRDA500S12	18.5 - 370	25 - 500	3/4
STATIONARY	TS30S4	TSD28S4	-	1.1 - 22	1.5 - 30	1/4
	TS150S6	TSD135S6	-	5.5 - 110	7.5 - 150	3/8
	TS300S8	TSD270S8	-	11 - 221	15 - 300	1/2
	TS1000S12	TSD1000S12	-	37 - 738	50 - 1000	3/4

JOINT SIMULATORS

ROTARY	Industry Standard	Includes Transducer	Joint Simulator Bolt Service Kit	ft-lb	Nm	in
	JKR20	No	JKS30-BKIT	0.75 - 15	1.0 - 20	1/4
	JKR75	No	JKS150-BKIT	2.8 - 55	3.8 - 75	3/8
	JKR180	No	JKS300-BKIT	6.7 - 133	9.0 - 180	1/2
	JKR500	No	JKS1000-BKIT	18.5 - 370	25.0 - 500	3/4
STATIONARY	JKS30	No	JKS30-BKIT	1.1 - 22	1.5 - 30	1/4
	JKS150	No	JKS150-BKIT	5.5 - 110	7.5 - 150	3/8
	JKS300	No	JKS300-BKIT	11.0 - 221	15 - 300	1/2
	JKS1000	No	JKS1000-BKIT	37.0 - 738	50 - 1000	3/4
	JKST30	TS30S4	JKS30-BKIT	1.1 - 22	1.5 - 30	1/4
	JKST150	TS150S6	JKS150-BKIT	5.5 - 110	7.5 - 150	3/8
	JKST300	TS300S8	JKS300-BKIT	11.0 - 221	15 - 300	1/2
	JKST1000	TS1000S12	JKS1000-BKIT	37.0 - 738	50 - 1000	3/4



٧	ww.inger	sollrar	nd.com



Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.