



2235 Series  
1/2" Impactool™



**REAL TOOLS FOR REAL WORK.™**

# The bar doesn't raise itself.

## The 2235 Series 1/2" Impactool™

A powerful, durable and reliable workhorse whose reputation is built on helping you build yours. It's been rigorously tested, beaten up, dropped and pushed to the limits to make sure it will always work when you need it most. The 2235 Series is incredibly powerful, durable and reliable so that it delivers every time you need REAL WORK done right.



General Automotive



General Industrial



Heavy Equipment Repair



Facility Maintenance

### Tool Features

#### DURABILITY

Born from the legendary durability of the Ingersoll Rand 2135 Series, the 2235 pushes toughness to the next level. It's built with a titanium hammercase, steel-wear plate and composite housing that protect the tool from the harshest environments.

#### POWER

Punish the toughest bolts with 1760 Nm. of nut-busting torque and 1220 Nm. of max reverse torque powered by Ingersoll Rand's finely tuned twin-hammer impact mechanism. From the garage to the most demanding industrial sites, there is no job that will stand in its way.



#### RELIABILITY

Every component, every mechanism and every function of the 2235 Series has been pushed to the limits to ensure it always performs in the face of the toughest jobs. Backed by a two-year warranty, the 2235 Series is a finely tuned workhorse, from its components to its technology, to be the impact wrench you can always count on to get REAL WORK done.

#### WEIGHT

At only 2.1 kg, no other impact wrench on the market can match the combined power and weight of the 2235 Series. With less weighing you down, you can work harder and faster for longer stretches of time.

### Specifications

2235 Series 1/2" Impactool™									
Model	CCN	Drive Size, Type	Max Torque (Nm)	Nut-Busting Torque (Nm)	BPM	Free Speed (rpm)	Weight (kg)	Length (mm)	Sound Level dB (A)
2235QTiMAX	47517574001	1/2" (50 mm)	1220	1760	1220	8500	2.1	193	88.7
2235QTiMAX-2	47517884001	1/2", 2" Ext. (50 mm)	1220	1760	1220	8500	2.3	244	88.7

Performance at 6.2 bar (90 PSI). Air inlet NPTF 1/4" (6mm). Min hose size 3/8" (10mm). Average air consumption 6 cfm (170 l/min) – at load 24 cfm (680 l/min)



irtools.com/2235  
**REAL TOOLS FOR REAL WORK.**

Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining comfortable and efficient environments. Our people and our family of brands — including Club Car®, Ingersoll Rand®, Thermo King® and Trane® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$12 billion global business committed to a world of sustainable progress and enduring results.