











2145QIMAX 3/4" AIR IMPACTOOL™ Maximum Impact

MAXIMUM IMPACT

More Power. Less Air. Not only does the new Ingersoll Rand® 2145QiMAX Impactool™ deliver incredible performance and industrial-grade durability, its efficient air motor also reduces air consumption — which saves you money.

MAX POWER

1350 ft-lb maximum reverse torque from a tool that weighs just 7.4 lbs and is compact enough to access tight spaces

MAX DURABILITY

Built to last and designed to withstand tough use in rugged environments; a two-year limited warranty is standard

MAX PRODUCTIVITY

An air motor that's 16% more efficient than its predecessor and an easy-to-clean inlet screen means less downtime, better tool performance, and less money spent on compressed air



Assembly and Disassembly of machinery and heavy equipment



Vehicle Service



Equipment Maintenance

	Specifications	2145QiMAX*	2155QiMAX
MAXIMUM	Drive	3/4"	1"
	Max Torque (Reverse)	1350 ft-lb (1830 Nm)	1350 ft-lb (1830 Nm)
	Forward Torque Range	200 - 900 ft-lb (271-1220 Nm)	200 - 900 ft-lb (271-1220 Nm)
	Blows Per Minute	1150	1150
	Maximum Free Speed	7000 rpm	7000 rpm
	Sound Pressure (free speed)	91.1 dBA	91.1 dBA
	Net Weight	7.4 lb (3.4 kg)	7.4 lb (3.4 kg)
	Overall Length	8.5" (217 mm)	8.8" (225 mm)
	Air Requirements		
	All Requirements		
	Average Air Consumption	8.5 cfm (241 L/min)	8.5 cfm (241 L/min)
	Air Consumption @ load	32 cfm (906 L/min)	32 cfm (906 L/min)
	Air Inlet	1/2" NPTF	1/2" NPTF
	Min Hose Size	1/2" (13 mm)	1/2" (13 mm)
	*Available in 3" and 6" extended	anvils.	

2145QIMAX 3/4" AIR IMPACTOOL™



► Patented Quiet Tool technology

reduces sound levels without compromising best-in-class power performance





