



2135QTL-2

*1/2" Torque Limited Impact Wrench*



# Put Power in its Place.

Don't let overtightened lug nuts damage customers' wheels or your reputation. The 2135QTL-2 delivers 780 ft lbs of max reverse torque to get lugs off in a hurry but limits forward torque to 75 ft lbs to avoid stress on the wheel studs and overtightening. It reaches target torque in just 2–3 seconds, is quiet on the job and weighs in at only 4.3 lbs. Driven by a finely tuned impact mechanism and motor that bleeds air instead of delivering a glancing blow, the 2135QTL-2 is 3X more durable than our previous torque limiting impact wrenches. Engineered as the ultimate torque wrench counterpart, the 2135QTL-2 is built for convenience and quality.

## Features



2135QTL-2 1/2" Torque Limited Impact Wrench

Model	Drive Size, (Type)	BPM	MAX Torque ft-lb. (Nm)	Free Speed RPM	Weight lb (kg)	LxWxH in. (mm)
2135QTL-2	1/2" (Square)	1,250	780 (1058)	11,000	4.3 (2)	9.5 x 2.7 x 7.2 (242 x 70 x 183)



IRCO.com

Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is committed to helping make life better. We provide innovative and mission-critical industrial, energy, medical and specialty vehicle products and services across 40+ respected brands designed to excel in even the most complex and harsh conditions where downtime is especially costly. Our employees connect to customers for life by delivering proven expertise, productivity and efficiency improvements.

We are committed to using environmentally conscious print practices.  
©2020 Ingersoll Rand IRITS-0119-010